



# JR. OLYMPIC VAULT VALUES FOR LEVEL 9

(Effective August 1, 2013 - July 31, 2017)

Revised August 28, 2014 Changes/additions are in Bold italics (Modified for OHSAA 2015-2016)

GROUP I HANDSPRINGS , YAMASHITAS	GROUP II HANDSPRINGS with or without 1/1 TURN - SALTO FORWARD OR BACKWARD	GROUP III TSUKAHARA or ½ on - SALTO FWD OR BWD with or without TURN	GROUP IV Round - off, Flic-flac on - SALTO FWD OR BWD with or without LA TURN	GROUP V Round - off, Flic-flac with ½ or 1/1 turn on - HANDSPG or SALTO FWD OR BWD with or without LA TURN
1.101 Handspring 8.6 1.102 Hndspring- ½ 8.7 1.103 Yamashita 8.6 1.104 Yami - ½ 8.7 1.105 ½ on -½ off 8.7 OR ¼ on - ¾ off 1.106 ¼ - ½ on - Repulsion off 7.0		<i>Note for the J.O. Program:</i> All Group 3 vaults may be performed with a 90° to 180° LA turn in the first flight		All Group 5 vaults described as a flic-flac with a 1/1 (360°) turn on may be performed with a ¾ (270°) to 1/1 (360°) LA turn in the first flight
1.201 Hsp - 1/1 9.0 1.202 Hsp - 1½ 9.4 1.203 Yami - 1/1 9.0 1.205 ½ on - 1½ off 9.3 or ¼ on - 1¾ off 1.206 ½ on - 1/1 off 8.9 or ¼ on - 1¼ off 1.207 1/1 on - H/Y 9.0 1.208 1/1 on - ½ off 9.3		3.201 Tsukahara Tuck 9.6	4.101 RO,FF on – Repulsion off 8.7* 4.102 RO,FF on – Repulsion ½ off 7.7 4.201 RO,FF on - 1/1 twist off 9.1 4.202 RO,FF on - 1½ twist off 9.3 (Allen) 4.203 RO,FF on - Back Tuck 9.6	5.101 RO,FF ½ on – Hndspg off 8.9  5.201 RO,FF ½ on - 1/1 twist off 9.2 5.202 RO,FF ½ on - 1½ twist off 9.4 5.207 RO,FF 1/1 on - 1/1 twist off 9.3
1.301 Hsp - 2/1 9.9 1.306 ½ on - 2/1 off 9.8 or ¼ on - 2¼ off 1.307 1/1 on - 1/1 off 9.7	2.301 Hsp - Front Tuck 10.0 2.302 Hsp - Front Tuck ½ 10.0 2.304 Hsp - Front Pike 10.0 2.310 Fr. Hndsp onto board, Hsp. – Fr. Tuck (llg) 10.0 2.311 Fr. Hndsp onto board, Hsp. – Fr. Pike (Garbarino) 10.0	3.302 Tsuk Tuck 1/1 10.0 3.303 Tsuk Pike 9.7 3.304 Tsuk layout 10.0 3.306 ½ on - ½ off, Fr. Tuck 10.0 or ¼ on - ¼ off, Fr. Tuck (land facing out) or Tsuk tuck ½ 3.308 ½ on - ½ off, Fr. Tuck ½ 10.0 (Shible) or ¼ on - ¾ off, Fr. Tuck ½	4.301 RO,FF on - 2/1 twist off 9.8 (Allen) 4.303 RO,FF on - B. Tuck 1/1 10.0 4.304 RO,FF on - B. Pike 9.7 4.305 RO,FF on - B. Layout 10.0 4.306 RO,FF on –B. Layout 1/1 10.0* 4.307 RO,FF on - ½ off, Fr. Tuck 10.0 or RO,FF on - B. Tuck ½  4.407 RO, FF on - ½ turn off, Fr. Tuck ½ (Beckman) 10.0	<b>5.301 RO,FF ½ on - Front Tuck 10.0</b> 5.312 RO,FF ½ on - 2/1 twist off 9.9

\* OSHAA Modification Only for 2015-2016 Competition Year